

FP-ECOFIX Rapid Set Fence Post Concrete

1. Identification

1.1 Introduction

Carlton FP-ECOFIX is a factory produced rapid set fence post concrete that sets in 5 to 10 minutes consisting of dried sands, cement and other additives.

1.2 Authority

Carlton FP-ECOFIX is manufactured under a registered ISO 9001 Quality System.

Materials used comply with the following standards:

Aggregate	BS EN 13139
Cement	BS EN 197-1

Admixtures do not contain calcium chlorides.

Water added on site should be clean and free from impurities.

2. Description

2.1 Manufacture

All raw materials and end products are subject to regular quality control procedures and testing.

Dried sand and other materials are weighed and mixed under computer control with rigorous quality control procedures.

3. Packaging

Carlton FP-ECOFIX is available in 20Kg plastic bags that are showerproof and recyclable.

4. Mixing Instructions

- Dig hole to correct depth and width relevant to post size.
- Fill hole approximately a third of depth with water and place post in hole.
- Pour in Carlton FP-ECOFIX evenly around the post until no standing water is visible.
- Position and level post as required. Setting will take place in 5 to 10 minutes.
- **Do not** mix Carlton FP-ECOFIX with water by hand or machine.

5. Conditions of Use

- Carlton FP-ECOFIX may be used to fix all types of wood, metal and concrete posts.
- Carlton FP-ECOFIX may be used for fixing decking posts, rotary washing lines and small/medium sized gateposts (less than 1.0m width gate).
- If a particular compressive strength is required, Carlton FP-ECOFIX should not be used.
- Recommended temperature range for use is 5°C to 30°C.
- Standard site practice to the relevant British and European Standards should always apply. Carlton Manufacturing cannot be held responsible where workmanship has not been carried out in accordance with good practice.

6. Prices and Conditions of Sale

Our Sales Office will be pleased to provide quotations for specific projects. All quotations are subject to our Conditions of Sale, a copy of which is available on request.

7. Health & Safety

For health & safety information – see Material Safety Datasheet.

8. Technical Services

8.1 Advisory Service

Our Technical Advisory Service is available to give expert advice on the specification or use of Carlton FP-ECOFIX.

